

posDiGi[®]

Model: RP80

Think Retail...Think posDiGi[®]

Thermal POS/Receipt Printer

Highlights:

- High Speed low noise printing upto max 250mm/s
- High Resolution printing upto 203 dpi
- Dual Interface (USB + Parallel) optional Serial/WiFi
- Built-in Auto-cutter
- 3 inch (80mm) print width
- Paper near end & end sensors
- Full Coverage Warranty



RT670B
Laser Scanner



RT410
Cash Drawer

Specification

Print Method: Direct Thermal Printing
Print Speed: 250 mm/sec
Print Resolution: 203 dpi
Sensor: Paper end/near end , Paper cover open
Paper Width: 80mm
Drop-in paper load
Printing Character: ASCII Font A: 12x24
ASCII Font B: 9x24
Character: 12x24
Barcode: Can print all 1D & 2D
Paper Roll: 80mm Width, max 83mm Dia
Printer Density: 512 dot/line or 576 dot/line
NV bitmap Flash: 64 kb, Receipt Buffer: 8 kb
TPHead: 15,000,000 lines/100 km
Auto-cutter: 1,000,000 cuts
MCBF: 60,000,000 lines
Input Voltage: AC 100 to 240V, 50/60Hz
Output Voltage: DC 24V, 2.5A
Operating Temp/Humidity: 0 to 45 C/ 10 to 80%
Storage Temp/Humidity: -10 to 50 C/ 10 to 90%
Certification: CE, FC, CCC
Emulation: ESC/POS
Driver: Windows 2000/XP/7/8
Cash Drawer: 1 port (24V DC)
Printer Dimension(WxLxH): 145x195x148mm
Weight: 1.3kg



posDiGi[®]

www.posdigi.com

High Speed Thermal Printing

posDiGi printers. Superior cost efficient, reliable printers.



Retail



Hospitality



Ticketing



Kiosk